1.0 1.1 2.0 2.2 <u>3.0</u> 3.1	machine connection: drain connection hose, DN 22 hose fitted as odour trap in interior of machinedrain (max. 700 mm above finished floor level), DN 50Machine connection: fresh water supply, G 3/4"Soft cold water 10°C, DN 15, G 3/4 a max. 0,54 mmol/I CaCO ₃ (max. 3°dH)Flow rate: 3 l/min Minimum flow pressure: 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5,0 bar stopcock and fine screen $\leq 25 \mu m$ Machine connection: electrical connection cable 5G 2,5mm²electricity supply to the machine: 3N PE 400V ~ 50Hz nominal current / - capacity: 15,7 A / 6,9 kWFuse protection: 16 A			35 700 710 - 735		۲۶ ۲۶ 50 550	330 56 52 52
6.1 all ca the po Mac (A) Et	Voltage equalising cable The master switch must be provided on site Heat load of warewash area for 20 programme cycles/h total 2,1 kW, perceptible 1,4 kW, latent 0,7 kW bles, pipes etc leaving machine 1,6 m position of the connection piping can also be mirror-inverted! Chine Equipment ntry height rinse dosing unit with suction lance (blue connector) gent dosing unit and suction lance	260 80 1.1 2.2 3.1	600 80	600			3.0
		MEIKO AUST HETMANEKG TEL. +43 1 69 E-MAIL: officer This drawing may not be neither passed to t for competitive purposes without our consen make changes resulting from technical prog is not subject to the checking and any releas management. Please note:	ASSE 1B, A-1230 WIE 92039 TELEFAX +43 @meiko.at hird parties for their informatio t. All rights reserved. We rese ess. This drawing was compu	1 699203923 n or copied or used rve the right to ter generated and	Revision Reference DISHWA STANDA TYPE: G Drawing-No. S000904	RD DRAWING / CZE LASSES	Type M-ICLEAN UM M2 Order-No.

Please note: This document is only valid in conjunction with the conditions defined in Supplementary Sheet "Important Information". These can be requested from the manufacturer or downloaded from the Partnernet.

M000025480.2.5 COPYRIGHT by MEIKO Scale

drawn:

15.08.2020 m-iplan

EN

COPYRIGHT by MEIKO

checked:

15.08.2020 m-iplan